

# RINK BRUSH SPREADERS

topdressing

The Rink brush topdressers most accurately "shoots" the material with force between the grass blades.

Model Rink	SP950 walk-in-front	TB950 pulled	Utility Vehicle model		1005	1010	1210	1520	1622	3045
	Self-propelled	towed version	for Cushman Turf Truckster	for John Deere Prologator/ Toro Workman	3-point hitch version	towed version	towed version	towed version	towed version	towed version
Spreading width	0.95m (37")	0.95m (37")	1.80m (71")	1.80m (71")	1.50m (59")	1.50m (59")	1.80m (71")	1.40m (55")	2.0m (79")	2.0m (79")
Spreading thickness	0.3 to 10mm	0.3 to 10mm	0.3 to 10mm	0.3 to 10mm	0.3 to 10mm	0.3 to 10mm	0.3 to 10mm	0.3 to 40mm	0.3 to 40mm	0.3 to 40mm
Weight	280kg (616lbs)	190kg (418lbs)	300kg (660lbs)	300kg (660lbs)	200kg (440lbs)	270kg (594lbs)	370kg (814lbs)	950kg (2090lbs)	1062kg (2341lbs)	1950kg (4290lbs)
Hopper capacity level	0.33m <sup>3</sup>	0.33m <sup>3</sup>	1.0m <sup>3</sup>	1.0m <sup>3</sup>	0.75m <sup>3</sup>	0.75m <sup>3</sup>	1.0m <sup>3</sup>	2.0m <sup>3</sup>	2.2m <sup>3</sup>	4.5m <sup>3</sup>
Tractor size	self-propelled 6.5hp engine	Any pull vehicle			25hp +:	20hp +:	20hp+:	25hp+:	35hp +:	65hp +:
					12l/ min@120bar	12l/ min@120bar	20l/ min@140bar	25l/min@ 140bar	25l/min@ 140bar	40l/min@ 175bar

**Optional items:** Auxiliary tank and pump unit (Rink 1010, 1210, 1520) / Own 13hp engine (Rink 1010, 1210, 1520) / 4 pivoting wheels (Rink 1520) / Dry sand plate (Rink 1204, 1205, 1005, 1010, 1210)

## Rink SP950 walk-in front



The Rink SP950 contains a 6,5hp engine, and the weight of the machine is evenly distributed over 6 wheels in order to minimize ground pressure.



The Rink TB950 is a wheel driven topdresser and can be pulled by virtually any vehicle. The brush and conveyor belt are driven by the 4 wheels (or optional by 2 wheels), ensuring a constant application rate.



A Quad or ATV easily operates the Rink TB950 pulled.

## Rink TB950 pulled

