

Specifications\*

<b>Model</b>		<b>CM244GC</b>
<b>Transmission</b>		Hydrostat
<b>Engine</b>	Type	3 cylinder water cooled diesel
	Gross power SAE HP (kW) / DIN HP (kW)	20 (27) / 18 (24)
	Displacement	cc 1123
	Rated speed	rpm. 2600
	Fuel tank capacity	l. 30
<b>Drive</b>	Number of forwards / reverse speed	1 / 1
	Forward speed	0-15
	4-WD	automatic, permanent
	Differential lock	standard
	Steering type	hydrostatic
<b>PTO independent</b>	Cruise Control	standard
	Front pto (mower deck)	rpm. 2000
	Side pto (blower)	independent selectable
<b>Dimensions</b>	Length	mm. 2330
	Width	mm. 1195
	Height	mm. 1450
	Gewicht	kg. 645
	Wheelbase	mm. 1110
<b>Tires</b>	Front	20 x 10.00 - 8
	Rear	210 / 60D - 8
<b>Mower deck</b>	Type mower deck	kg Rear / Mulch
	Cutting width	mm. 137
	Number of blades	3
<b>Collector</b>	High dump system	Hydraulic
	Capacity	l. 550
	Max. lifting height	mm. 1900
	Drive ventilator	Axle

\*The specifications are subject to change without notice.

FRONTMOWER WITH COLLECTOR

CM244GC

SHIBAURA



⚠ Important information

• Improper use of any product may cause serious or fatal injury. Read, understand and follow carefully the operating and safety instructions in your owner's manual before using such products.

**SHIBAURA**

SHIBAURA EUROPE BV  
 Begonialaan 7  
 NL - 6851 TE Huissen  
 T. 0031 (0)26 326 9999  
 F. 0031 (0)26 326 9990  
 E. info@shibaura.com  
 I. www.shibaura.com

Dealer:

ittec s.r.o. ④  
 Za Šmalíkem 824, 149 00 Praha 4  
 provozovna - zasilatelská adresa:  
 AOS Modletice 106, 251 01 Říčany  
 tel. 323616222 fax 323616223  
 DIČ CZ64574296, www.ittec.cz





Well-organized dash board:



Mower deck can be flipped up to maintain blade and clean inside deck easily. Excellent cut quality is achieved by a PTO driven 2-blade, which in turn against each other, mowerdeck.




User can reach engine room easily for daily maintenance.



The spacious operator platform provides plenty of foot and leg.



Steering column can be tilted and power steering is standard equipment.



Cruise Control for variable speed setting is included as standard. Two levers for heffen en openen of the collector.



Easily cleaning of the screen for dust-free sucking up of cooling air.